




48V-S Track




230V Track



48V DALI Track



230V DALI Track



AURORE D40 TRACK



AUORE D40 • 48V-S Track • 230V Track • 48V DALI Track • 230V DALI Track

Range	Highly flexible spotlight on track for general & accent lighting	
Description	Low luminance Rotation 360° - Adjustable tilt 90° Optional : Easily changeable LED, optics and accessories on site, without any tool, with integrated Easy Swap system (see page 6)	
Finish	White RAL 9003 matt finish Black RAL 9005 matt finish (other upon request)	
Dimensions	48V Stucchi Track	230V Track
	Spotlight diameter : 40mm Height : 90mm Driver length : 98mm Track dimensions : 26.4 x 21mm	Spotlight diameter : 40mm Height : 90mm Driver length : 162mm Track dimensions : 31.5 x 32.5mm
	48V DALI Track	230V DALI Track
	Spotlight diameter : 40mm Height : 90mm Driver length : 166mm Track dimensions : 26.4 x 21mm	Spotlight diameter : 40mm Height : 90mm Driver length : 253.5mm Track dimensions : 31.5 x 32.5mm
Net weight	± 0.3 kg according to version	
LED characteristics	48V	230V
	MacAdam ellipse : 3 SDCM (standard) 2 SDCM (premium)	MacAdam ellipse : 3 SDCM
	2700K - 3000K – 3500K – 4000K – 5000K (other upon request) CRI90 (standard version) – CRI95, R9 > 80	
Optical beams	6° - 10° - 15° - 20° - 25° - 30° - 35° - 40° - 55° - 60° - Elliptical UGR < 15	
Accessories	Filters, honeycomb grid upon request	
Luminous flux	300 to 800 lumen according to version	
Power supply	48V-S Track	230V Track
	Spot adaptor for 48V track 48V power supply on the spotlight	230V power supply on the spotlight Track adapter suitable for Global Trac PRO XTS or similar (ERCO, Trajectoire...)
	48V DALI Track	230V DALI Track
	Spot adaptor for 48V track 48V DALI power supply on the spotlight Dimming by pwm	230V DALI power supply on the spotlight Track adapter suitable for Global Trac Pulse, STUCCHI, SLV...
For USA & Canada use UL class 2 power supply		

All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged




AUORE D40 • 48V-S Track • 230V Track • 48V DALI Track • 230V DALI Track

Power	4W to 10W according to version
Electric class	48V tracks : class 3 230V tracks : class 2
Use limitations	The product must be installed in a ventilated area Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees The drivers, if not delivered by LOuss, must be approved before use
Warranty	Life span : L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature 3-year parts and labour warranty The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lightning injury, as well as the normal wear of the product All products are electrically tested and received a functional burn-in.





AURORE D40 48V-S TRACK



AURORE D40 230V TRACK

Track Global Trac PRO
Warning: Dimensions may vary by a few mm from one manufacturer to another



Louss

All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged

Last update : 2025/06/19

4/6

Firalux & LOuss brands


SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group


Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE



AURORE D40 48V DALI TRACK



AURORE D40 230V DALI TRACK



Louss

All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged
Last update : 2025/06/19

5/6

Firalux & LOuss brands

SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE



AUORE D40 • 48V-S Track • 230V Track • 48V DALI Track • 230V DALI Track

Easy swap system



All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged

Louss

Last update : 2025/06/19

Firalux & LOuss brands

SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE