



AURORE D82 TRIMLESS

*Tunable White Version
2700K-6500K*





AURORE D82 TRIMLESS

Tunable white version 2700K-6500K

Range	Highly flexible recessed ceiling downlight for general & accent lighting
Description	Low luminance Rotation 360° - Adjustable tilt 45° + 45° White mat finish RAL 9003 (other upon request)
Net Weight	0.9 kg
Installation	Installation diameter: 165mm No specific tools required
LED characteristics	3 LED 2700K – 4000K – 6500K Output luminous flux between 2300 to 2600 lumen
Optical beam	8°- 20°- 30° UGR < 15
Connection	Supplied with 0.50m 6-conductors cable In option : daisy-chain (2 input-output cables for serial cabling)
Separate power supply	Remote constant current DMX driver 350mA to 700mA (1A possible with driver flanged at 30W max)
Power consumption	Luminaire : 25W max 30W max driver included
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (At) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 5-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged.

LOuss

Last update: 30/07/2021

Firalux & LOuss brands

SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z


Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE

AUORE D82 TRIMLESS

Tunable white version 2700K-6500K

CABLAGE AURORE D82 TUNABLE WHITE DMX DAISY CHAIN VERSION



Each spot

4 LED 2700K 700 mA/12V 8.4W
 4 LED 4000K 700mA/12V 8.4W
 4 LED 6500K 700 mA/12V 8.4W
 Total 25.2W

Daisy chain version : 2 x cable
 with 6 conductors 0.5m

⊗ Depend of the driver characteristic
 For each spot we need 700mA /12V/25W output
 With ELDOLED 100W : $P_w = 100w$ $V_{out} < 57V$
 So we can connect less than 4 spots / driver
 With ELDOLED 50W : $P_w = 50W$ $V_{out} < 55V$
 So we can connect 1 or 2 spots / driver

All the connections have to be made before powering up,
 otherwise the luminaires could be seriously damaged.

LOUSS

Last update: 30/07/2021

Firalux & LOUSS brands

SARL, Capital 40 000€
 RCS DIJON B 503 367 245
 TVA/VAT n°: FR24 503 367 245
 APE 4676Z

Tel. : +33 380 48 65 68
 contact@louss.fr
 www.louss.fr
 Best group

Siège social / Head Office
 PA Les Terres d'Or
 Route de Saint Philibert
 21220 Gevrey Chambertin - FRANCE