















### SCAPINI • SCAPINI S3 • SCAPINI S4

Range	Scapini S3	Scapini S4
	Spotlight for accent lighting	Spotlight for ambient lighting
Description	Black or natural anodized aluminum body Directional bracket	
Dimensions & Weight	Scapini S3	Scapini S4
	Spotlight length : 237mm Spotlight width : 140mm	Spotlight length : 325mm Spotlight width   : 200mm Bracket width    : 150mm
	6.6 kg	xxx kg
LED characteristics	Scapini S3	Scapini S4
	6 LEDs : 3000K – 4000K (other upon request)	18 LEDs : 3000K – 4000K (other upon request)
Optical beams	6° - 15° - 35° (other upon request)	
Connection	Supplied with 0.5m cable (more length upon request) 230V direct connection	
Integrated Power supply	230 Vac For the US & Canada, use UL class 2 driver	
Power	Scapini S3	Scapini S4
	15W max.	50W max.
	The product must be installed into a ventilated area.	
Use limitations	Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees	
	The drivers, if not delivered by LOuss, must be approved before use	
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature.	
	3-year parts and labor warranty	
	The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product	
	All products are electrically tested and received a functional burn-in	

All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged.
Last update : 2025.07.01

Firalux & LOuss brands

2/3

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z

lOuss

Tel. : +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE



#### **SCAPINI S3**





# All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

## lOuss

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z

#### Last update : 2025.07.01

Tel. : +33 380 48 65 68 contact@louss.fr www.louss.fr Best group 3/3 Firalux & LOuss brands

Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE