

Wouss



Lighting Emotion



ALBEDIO 180

*The recessed down light
large model*





ALBEDIO 180

Range	Integrated ceiling spotlight for ambient lighting
Description	Body in aluminium, white painting finishing Springs mounting Low luminance
External diameter	180mm
Net Weight	0.518 kg
LED characteristics	6 LED – 12 LED: 3000K – 4000K (other LED colours upon request) 12 LED: TW - RGBW
Optical beam	15° - 30° - 40° - 60° (other optical beam upon request)
Connection	Delivered with 0.5m standard cable (more length upon request) Individual connection or connection in series on external constant current driver
Separate power supply	6 LED: 350mA – 500mA 12 LED : 350mA
LED power	350mA : 7.2W (6 LED) - 10.8W (12 LED) 500mA : 11W (6 LED)
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up,
otherwise the luminaire could be seriously damaged.

LOuss

Last update : 15/12/2021

Firalux & Louss brands

SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE