





ALBEDIO 80

The small adjustable downlight





















ALBEDIO 80

Range	Recessed ceiling spotlight for ambient lighting
Description	Body in white, grey or black aluminium
	Adjustable mounting with springs
	30° adjustable
Dimensions	External diameter: 83mm
	Installed depth: 76.5mm
Weight	0.191 kg
LED characteristics	3 LED: 3000K - 4000K (other LED colours upon request)
	3 LED: RGB
	4 LED: TW
	T LLD. IVV
Optical beam	15° - 35° - 60° (other optical beam upon request)
Connection	Delivered with 0.5m standard cable (more length upon request)
	Individual connection or connection in series on external constant current driver
Separate power supply	350mA - 500mA
LED power	350mA: 3.6W (3 LED) - 4.8W (4 LED)
	500mA : 5.4W (3 LED) = 4.8W (4 LED)
	300HA : 5:4VV (3 LED) - 7:2VV (4 LED)
Use limitations	The product must be installed into a ventilated area. Any use with an ambient
	temperature higher than the specified ambient temperature (Ta) would lead to a more
	rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.
The divers, if het delivered by Leads, mast be approved before asc.	
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty.
	The warranty does not apply to products that have been opened, modified or repaired
	and does not cover the effects of a wrong connection, careless, abusive handling,
	overvoltage, lighting injury, as well as the normal wear of the product.
	All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up, otherwise the luminaire could be seriously damaged.



Last update: 20/09/2018

Firalux & LOuss brands