

ANELO 50

The outdoor floodlight which thrives indoor





















ANELO 50

| Range | Surface mounted architectural floodlighting |
|-----------------------|--|
| Description | Body in natural anodised aluminium (other finishing upon request) Transparent polycarbonate protector, treated to withstand UV Stainless steel bracket |
| External diameter | 50mm |
| Net Weight | 0.22 kg |
| LED characteristics | 1 LED: 2200K - 2700K - 3000K - 4000K - 5000K - 6500K (other LED colours upon request) |
| Optical beam | 6° - 15° - 35° (other optical beams upon request) |
| Connection | Delivered with 1m standard cable (more length upon request) Individual connection or connection in series on external constant current driver |
| Separate power supply | 350mA – 500mA – 700mA |
| LED power | 350mA: 1.2W 500mA: 1.8W 700mA: 2.4W |
| Use limitations | The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use. |
| Warranty | Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in. |

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

Wuss

Last update: 01/02/2019

Firalux & LOuss brands