



RECESSED ON-PLATE



TRIM



TRIM FLUSH



TRIMLESS



TRIMLESS FLUSH



TRIMLESS MAGNETIC

AURORE D40 RECESSED




Range	Highly adjustable recessed ceiling downlights for general & accent lighting		
Description	Low luminance Rotation 360° Trim, Recessed On-plate, Trimless & Trimless Magnetic : Adjustable tilt 30° Trim Flush & Trimless Flush : Adjustable tilt 20° Optional : Easily changeable LED, optics and accessories on site, without any tool, with integrated Easy Swap system (see page 9)		
Finish	White RAL 9003 matt finish Black RAL 9005 matt finish (other upon request)		
Dimensions	Trim	Trim Flush	Recessed On-plate
	Spotlight diameter : 40mm	Spotlight diameter : 40mm	Spotlight diameter : 40mm
	External diameter : 83.5mm	External diameter : 93.5mm	External diameter : 60mm
	Installation diameter : 67.5mm	Installation diameter : 77.5mm	Installation diameter : 52mm
	Installation depth : 46mm	Installation depth : 78mm	Installation depth : 31mm
	Trimless	Trimless Flush	Trimless Magnetic
	Spotlight diameter : 40mm	Spotlight diameter : 40mm	Spotlight diameter : 40mm
	External diameter : 40mm	External diameter : 40mm	External diameter : 40mm
	Installation diameter : 67.5mm	Installation diameter : 77.5mm	Installation diameter : 67.5mm
	Installation depth : 48mm	Installation depth : 80mm	Installation depth : 48mm
Weight	± 0.15 kg according to version		
LED characteristics	2700K - 3000K – 3500K – 4000K – 5000K (other upon request) MacAdam Ellipse : 3 SDCM CRI90 (standard version) – IRC95, R9 > 80		
Optical beams	6° - 10° - 15° - 20° - 25° - 30° - 35° - 40° - 55° - 60° - Elliptical UGR < 15		
Accessories	Filters, honeycomb grids upon request		
Luminous flux	300 to 800 lumen according to version		
Connection	Supplied with 0.5m cable		
Power supply	Remote constant current driver 350mA to 700mA according to version Dimmable driver upon request		
Power	4W to 10 W according to version		




Use limitations	The product must be installed into a ventilated area Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees The drivers, if not delivered by LOuss, must be approved before use
Warranty	Life span: L80-B10 = 35,000 hours (80% remaining flux) at 30°C ambient temperature The warranty applies to components and fabrication supplied by Louss The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product All products are electrically tested and receive a functional burn-in



AURORE D40 RECESSED ON-PLATE



AURORE D40 TRIM



All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged

Louss

Last update : 2025/08/06

Firalux & LOuss brands



SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE





AUORE D40 TRIM FLUSH



Upper position

Insert the luminaire into the **upper position** of the recessed frame to obtain a **flush** luminaire





Low position

To obtain **30° orientation** angle, insert the luminaire in the **lowest position**


WARNING :
in this position, the spotlight cannot flush with the ceiling

AUORE D40 TRIM FLUSH EASY SWAP



Upper position

Insert the luminaire into the **upper position** of the recessed frame to obtain a **flush** luminaire



Low position

To obtain **30° orientation** angle, insert the luminaire in the **lowest position**

WARNING :
in this position, the spotlight cannot flush with the ceiling

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged

Louss

Last update : 2025/08/06

5/9

Firalux & LOuss brands



SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group



Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE



AURORE D40 TRIMLESS & TRIMLESS EASY SWAP





AURORE D40 TRIMLESS FLUSH



Upper position

Insert the luminaire into the **upper position** of the recessed frame to obtain a **flush** luminaire



Low position

To obtain **30° orientation** angle, insert the luminaire in the **lowest position**

WARNING :
in this position, the spotlight cannot flush with the ceiling

All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged

Louss

Last update : 2025/08/06

6/9

Firalux & LOuss brands



SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE



AURORE D40 TRIMLESS MAGNETIC



All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged

lOuss

Last update : 2025/08/06

7/9

Firalux & LOuss brands

SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z


Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE




AURORE D40 • TRIMLESS • TRIMLESS FLUSH • TRIMLESS MAGNETIC


Installation from above




Install the recessed frame from above and screw it into the surface




Cover the lateral plates of the recessed frame by coating and painting




Insert the spotlight from below




Installation from below




Install the recessed frame from below and screw it into the surface



Cover the lateral plates of the recessed frame by coating and painting



Insert the spotlight from below





RECESSED
ON-PLATE



TRIM



TRIM
FLUSH



TRIMLESS




TRIMLESS
FLUSH




TRIMLESS
MAGNETIC


Easy Swap system




Recessed frame
(according to version)




LED / COB



Luminaire's body



Optics



Insert

All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged

lOuss

Last update : 2025/08/06

Firalux & LOuss brands

SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE