



RECESSED ON-PLATE



TRIM



TRIM FLUSH



TRIMLESS



TRIMLESS FLUSH



TRIMLESS MAGNETIC

AURORE D40 RECESSED




Range	Highly adjustable recessed ceiling downlights for general & accent lighting		
Description	Low luminance Rotation 360° Trim, Recessed On-plate, Trimless & Trimless Magnetic : Adjustable tilt 30° Trim Flush & Trimless Flush : Adjustable tilt 20° Easily changeable LED, optics and accessories on site, without any tool, with integrated Easy Swap system (see page 9)		
Finish	White RAL 9003 matt finish Black RAL 9005 matt finish (other upon request)		
Dimensions	Trim	Trim Flush	Recessed On-plate
	Spotlight diameter : 40mm External diameter : 83.5mm Installation diameter : 67.5mm Installation depth : 46mm	Spotlight diameter : 40mm External diameter : 93.5mm Installation diameter : 77.5mm Installation depth : 78mm	Spotlight diameter : 40mm External diameter : 60mm Installation diameter : 52mm Installation depth : 31mm
	Trimless	Trimless Flush	Trimless Magnetic
	Spotlight diameter : 40mm External diameter : 40mm Installation diameter : 67.5mm Installation depth : 48mm	Spotlight diameter : 40mm External diameter : 40mm Installation diameter : 77.5mm Installation depth : 80mm	Spotlight diameter : 40mm External diameter : 40mm Installation diameter : 67.5mm Installation depth : 48mm
	2700K - 3000K – 3500K – 4000K – 5000K (other upon request)		
	MacAdam Ellipse : 3 SDCM CRI90 (standard version) – IRC95, R9 > 80		
Optical beams	6° - 10° - 15° - 20° - 25° - 30° - 35° - 40° - 55° - 60° - Elliptical UGR < 15		
Accessories	Filters, honeycomb grids upon request		
Luminous flux	300 to 800 lumen according to version		
Connection	Supplied with 0.5m cable		
Power supply	Remote constant current driver 350mA to 700mA according to version Dimmable driver upon request For USA & Canada use UL class 2 power supply		
Power	4W to 10 W according to version		


All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged



AURORE D40 RECESSED ON-PLATE



AURORE D40 TRIM



All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged

Louss

Last update : 2025/06/17

Firalux & LOuss brands



SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE





AUORE D40 TRIM FLUSH



Upper position

Insert the luminaire into the **upper position** of the recessed frame to obtain a **flush** luminaire





Low position

To obtain **30° orientation** angle, insert the luminaire in the **lowest position**


WARNING :
in this position, the spotlight cannot flush with the ceiling

AUORE D40 TRIM FLUSH EASY SWAP



Upper position

Insert the luminaire into the **upper position** of the recessed frame to obtain a **flush** luminaire



Low position

To obtain **30° orientation** angle, insert the luminaire in the **lowest position**

WARNING :
in this position, the spotlight cannot flush with the ceiling

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged

Louss

Last update : 2025/06/17

5/9

Firalux & LOuss brands



SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group




Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE



AURORE D40 TRIMLESS & TRIMLESS EASY SWAP




AURORE D40 TRIMLESS FLUSH



Upper position

Insert the luminaire into the **upper position** of the recessed frame to obtain a **flush** luminaire



Low position

To obtain **30° orientation** angle, insert the luminaire in the **lowest position**

WARNING :
in this position, the spotlight cannot flush with the ceiling

All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged

Louss

Last update : 2025/06/17

6/9

Firalux & LOuss brands



SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE



AURORE D40 TRIMLESS MAGNETIC



All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged

lOuss

Last update : 2025/06/17

7/9

Firalux & LOuss brands

SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z


Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE




AUORE D40 • TRIMLESS • TRIMLESS FLUSH • TRIMLESS MAGNETIC


Installation from above




Install the recessed frame from above and screw it into the surface




Cover the lateral plates of the recessed frame by coating and painting




Insert the spotlight from below




Installation from below




Install the recessed frame from below and screw it into the surface



Cover the lateral plates of the recessed frame by coating and painting



Insert the spotlight from below



8/9

Louss

Last update : 2025/06/17

Firalux & LOuss brands

SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE



RECESSED
ON-PLATE



TRIM



TRIM
FLUSH



TRIMLESS




TRIMLESS
FLUSH




TRIMLESS
MAGNETIC


Easy Swap system




Recessed frame
(according to version)




LED / COB



Luminaire's body



Optics



Insert

All the connections have to be made before powering up,
otherwise the luminaires could be seriously damaged

LOUSS

Last update : 2025/06/17

Firalux & LOUSS brands

SARL, Capital 40 000€
RCS DIJON B 503 367 245
TVA/VAT n°: FR24 503 367 245
APE 4676Z

Tel. : +33 380 48 65 68
contact@louss.fr
www.louss.fr
Best group

Siège social / Head Office
PA Les Terres d'Or
Route de Saint Philibert
21220 Gevrey Chambertin - FRANCE