



MAGMATO 40

The recessed architectural floodlighting Mini














Short model - max. 350mA

Ø32





MAGMATO 40

MAGMATO 40	
Range	Recessed architectural floodlighting
Description	Body in aluminium, head in stainless steel Armoured glass Dedicated recessed box
Dimensions	External diameter: 40 mm Length: 67.30mm (short model) or 91mm (long model)
LED characteristics	1 LED: 2200K - 2700K - 3000K - 4000K - 5000K - 6500K (other LED colours upon request)
Optical beam	15° - 35° - 40° - 60° (other upon request)
Connection	Delivered with 1m standard cable (more length upon request)
Separate power supply	Short model: 350mA constant current driver Long model: 350mA – 500mA – 700mA
Integrated power supply	Long model : 12V or 24V
LED power	350mA: 1.2W – Short and long model 500mA: 1.8W – Long model 700mA: 2.4W – Long model 12V or 24V: 1.5W – Long model
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

Wuss

Last update: 04/02/2019

Firalux & LOuss brands

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z

Tel.: +33 380 48 65 68 contact@louss.fr www.louss.fr Best group

Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE