















## ONE

Range	Accent or ambient lighting luminaire Designed by Benoit Lalloz
Description	Painted steel or satin-brushed metal finish body To be mounted on track
Dimensions	External diameter: 110mm
Weight	0.869kg (without rail)
LED characteristics	6 LED: 3000K – 4000K (other LED colours upon request)
Optical beam	6° - 15° - 35° (other optical beam upon request)
Connection	Universal adapter with 3 switches Integrated constant current driver
Integrated power supply	350mA – 500mA – 700mA
LED Power	350mA : 7.2W 500mA : 10.8W 700mA : 15W
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.

## All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.



Last update : 20/02/2020

Firalux & LOuss brands

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel. : +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE