



PAPILIO

The airy and elegant luminaire













PAPILIO

Range	Accent decorative luminaire
Description	Sophisticated and elegant LED luminaire specially designed for showcases. Mirror finish or bright gold finish Mounting system: M10/1
Dimensions	Head: 50.4x30mm Rod: Length: 100mm, 200mm or 333mm Diameter: 8mm
LED characteristics	2 LED: 2700K - 3000K - 4000K (other LED colours upon request)
Optical beam	15° - 25° - 40° - 80° (other optical beam upon request)
Connection	Delivered with 0.5m standard cable (more length upon request) Individual connection or connection in series on external constant current driver
Separate power supply	350mA – 500mA
LED Power	350mA: 2.4W - 500mA: 3.6W
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

Last update: 20/09/2018 Firalux & LOuss brands

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z

Tel.: +33 380 48 65 68 contact@louss.fr www.louss.fr Best group