





SATURNE

Ultra compact adjustable recessed luminaire





























SATURNE

| Range | Ultra compact recessed adjustable luminaire for accent lighting |
|-----------------------|---|
| Description | Anodized aluminum body Adjustable mounting system |
| Finish | Natural or black anodized (other finish upon request) |
| Dimensions | External diameter: 35mm Fits into 19mm thickness panel |
| Net weight | 0.022 kg |
| LED characteristics | 1 LED: 2700K - 3000K - 3500K - 4000K (other upon request) CRI 92 |
| Optics | 16°- 23° - 25° - 33° - 37° - 58° - 69° - 78° - 17°x49° |
| Connection | Delivered with 0.5m cable (other lengths upon request) Individual connection or connection in series on external constant current driver Daisy chain version available (male and female quick connectors) |
| Separate power supply | Remote constant current driver 500mA max For USA and Canada use a UL Class 2 driver |
| Power | 1.7W at 500mA max |
| Use limitations | The product must be installed into a ventilated area Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees The drivers, if not delivered by LOuss, must be approved before use |
| Warranty | Life span: L80-B10 = 35,000 hours (80% remaining flux) at 30°C ambient temperature The warranty applies to components and fabrication supplied by LOuss The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product All products are electrically tested and receive a functional burn-in |

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged

Last update: 2025.07.11

Wuss

Firalux & LOuss brands