





SCAPINI S1

The lighting with assertive design Small version





















SCAPINI S1

Range	Accent decorative luminaire
	Designed by Benoit Lalloz
Description	Body in anodised aluminium (natural or black)
	Directional bracket
Dimensions	See dimensional drawing
Net Weight	0.029 kg
LED characterisics	1 LED: 2700K - 3000K - 4000K (other upon request)
Outing the area	450, 200, 400, 200 (all-an artical language)
Optical beam	15° - 30° - 40° - 60° (other optical beam upon request)
Connection	Delivered with 0.5m standard cable (more length upon request)
	Connection in series on external constant current driver
Separate power supply	350mA – 500mA
LED power	350mA: 1.2W
	500mA: 1.8W
	The product must be installed into a ventilated area. Any use with an ambient
Use limitations	temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees.
	The drivers, if not delivered by LOuss, must be approved before use.
	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature.
Warranty	3-year parts and labour warranty.
	The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product.
	All products are electrically tested and received a functional burn-in.
	-

All the connections have to be made before powering up, otherwise the luminaire could be seriously damaged.

Last update: 20/09/2018

Firalux & LOuss brands

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel.: +33 380 48 65 68 contact@louss.fr www.louss.fr Best group