







## **SCOPIO**

The spotlight specially developed for museums























## **SCOPIO**

Range	Accent luminaire
Description	Body in natural anodised aluminium
<u>'</u>	Stainless steel bracket
Dimensions	External diameter: 30 mm
LED characteristics	1 LED: 3000K - 4000K (other LED colours upon request)
Optical beam	15° - 30° - 40° - 60° (other optical beam upon request)
Connection	Delivered with 0.5m standard cable (more length upon request)
	Individual connection or connection in series on external constant current driver
Separate power supply	350mA - 500mA - 700mA
	050 4 4004
LED power	350mA: 1.2W
	500mA: 1.8W
	700mA: 2.4W
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees.
	The drivers, if not delivered by LOuss, must be approved before use.
	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature.
	3-year parts and labour warranty.
Warranty	The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product.
	All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

Last update: 20/09/2018

**W**uss

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245

APE 4676Z

Tel.: +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE

Firalux & LOuss brands