



V30 PATELLA





















V30 PATELLA

Range	LED spot
Description	Body in black or natural anodised aluminium Special version Mirror Finish
Dimensions	Head length: 30.90mm - diameter: 30mm Rod length: 19mm
Weight	0.039 kg
LED characteristics	1 LED : 2700K - 3000K - 4000K (other LED colours upon request)
Optical beam	10° - 12° - 15° - 28° - 32° - 40° (other optical beam upon request)
Connection	Delivered with 20cm cable (more length upon request) Individual connection or connection in series on external constant current driver
Separate power supply	350mA - 500mA - 700mA
LED power	350mA: 1.2W 500mA: 1.8W 700mA: 2.4W (low luminance version)
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

Wuss

Last update: 20/09/2018

Firalux & LOuss brands

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel.: +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE