







V25 PATELLA

Range	Spotlight for accent lighting
Description	Ball joint spotlight black or natural anodised aluminium Rotation 360° Threaded rod M3x12
Dimensions	Length : 34mm Diameter : 25mm
Net weight	0.050 kg
LED characteristics	1 LED : 2200K - 2700K – 3000K – 3500K - 4000K (other upon request) CRI 80, 90 ou 95 R9>80 Filter, honey comb upon request
Optical beam	14°- 17°- 25°- 30°- 35°- 40°- 60°- Elliptical (other upon request)
Connection	Supplied with 0.5m cable (other length upon request) Individual or series connection to remote constant current driver
Separate power supply	350mA to 900mA max constant current driver Dimmable driver upon request
LED power	350mA : 1.2W - 500mA : 1.8W 700mA : 2.4W - 900mA : 2.7W
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

lOuss

Last update : 18/07/2022

Firalux & LOuss brands

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel. : +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE