






MYSTA 230V TRACK









MYSTA TRACK 230V

	→90∘				
Range	Adjustable low lum	Adjustable low luminance spotlight on track for general and accent lighting			
Description	Low luminance Rotation 355° - Adjustable tilt 90° Driver suitable for 3-circuits track Easily changeable LED, optics and accessories on site, without any tool, with integrated LOuss Permuto easy swap system (see page 3)				
Finish	White RAL 9003 matt finish Black RAL 9005 matt finish other upon request				
Dimensions & Net Weight	Spotlight diameter : 46mm Height : 145mm (driver and fixing device included) 0.250 kg				
LED characteristics	2700K - 3000K - 3500K - 4000K - 5000K (other upon request) MacAdam ellipse : 3 SDCM (standard version) - 2 SDCM (premium version) CRI90 (standard version) - CRI95, R9 > 80 (premium version)				
Optical beams & Performances	Beam	Candela	Power	Photometry	
	11°	10 900cd (3000K)	7W	les 2591A	
	16°	6 300 cd (3500K)	8W	ies 2645A	
	20°	4 400 cd (3500K)	7W	les 2510A	
	23°	3 100 cd (3500K)	7W	ies 2511A	
	34°	1 700 cd (3500K)	8W	ies 2617B	
	43°	1 050 cd (3500K)	7W	les 2513A	
	300 to 800 lumen UGR < 15				
Accessories	Filters, honeycomb grid upon request				
Power	4W to 10W according to version				
Power supply	Driver suitable for Global Trac Pro XTS track or equivalent (Erco, Trajectoire)				
Use limitations	The product must be installed into a ventilated area Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees The drivers, if not delivered by LOuss, must be approved before use				
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product All products are electrically tested and received a functional burn-in				

Wuss

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged

Last update: 2025/06/13 Firalux & LOuss brands

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel.: +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE

2/3



MYSTA TRACK 230V



LOuss **Permuto** – Easy swap system



All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged

Wuss

Last update: 2025/06/13

Firalux & LOuss brands

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel.: +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE

3/3