







IK10 LINEAR









IK10 LINEAR

Range	Recessed linear light	
Description	Aluminum profile integrated in a stainless steel U support	
	Polycarbonate diffuser	
Finish	RAL upon request	
Dimensions	Profile	Integrating U
	Width: 43mm	Width: 50mm
	Height: 47mm	Height : 50mm
	Length from 500mm to 2,500mm max. – Cut-out size 100mm	
Net weight	Profile : 4 kg/m	
	Integrating U: 3.3kg/m	
LED characteristics	2700K - 3000K - 3500K - 4000K - 5000K (other upon request)	
	CRI80 ou 90 (95 upon request)	
	MacAdam 3 steps	
Luminous flux	2500 lumen max. per meter	
Connection	5m maximum in series	
Power supply	24V separate power supply	
	For the US & Canada use a UL class 2 driver	
LED power	30W/m max.	
Use limitations	The drivers, if not delivered by LOuss, must be approved before use	
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature	
	3-year parts and labor warranty	
	The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product	
	All products are electrically tested and received a functional burn-in	

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged

Wuss

Last update : 2025.08.06

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel.: +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE

Firalux & LOuss brands